

PB-3

PRIKLJUČNA KOMORA ZA VARIABILNI VRTINČNI DIFUZOR PLENUM BOX FOR VARIABLE SWIRL DIFFUSER

OPIS:

Priključna komora PB-3 se uporablja v kombinaciji z variabilnimi vrtninčnimi difuzorji tipa VSD-1, VSD-2, TWIST AIR in ED.

KONSTRUKCIJA: komora je valjaste oblike z okroglo priključno odprtino na vertikalni ali horizontalni poziciji in obešali za pritrditev pod strop.

MATERIAL:

- pocinkana pločevina
- nerjaveča pločevina INOX AISI 304

DODATKI:

Na zahtevo kupca se komori lahko dodajo:

1. prečka z M6 matico za pritrditev difuzorja
2. perforirana razpršilna plošča
3. loputa z zunanjo in notranjo ročico
4. tesnilni obroč na priključku
5. izolacija 6, 10, 13 ali 19 mm na zunanji strani ohišja
6. izolacija 6, 10, 13 ali 19 mm na notranji strani ohišja

DESCRIPTION:

Plenum box PB-3 is used as supplement to variable swirl diffusers VSD-1, VSD-2, TWIST AIR, and ED.

CONSTRUCTION: PB3 consists of a round casing with a round connection opening at horizontal or vertical positions and hangers for montage under the ceiling.


MATERIAL:

- galvanized sheet metal
- stainless steel sheet metal INOX AISI 304

SUPPLEMENTS:



Per customer's request, the following can be added:

1. traverse for mounting the diffuser
2. perforated dispersing plate
3. damper with handle inside and outside
4. sealing ring on the connection opening
5. ISO - insulation 6, 10, 13 or 19 mm on the outside or on the inside of the casing
6. ISO - insulation 6, 10, 13 or 19 mm on the outside or on the inside of the casing



DIMENZIJE / DIMENSIONS:

	100	125	160	180	200	250	315	355	400	500	630
øD	100	125	160	180	200	250	315	355	400	500	630
øD3	98	98	123	158	158	198	248	313	313	398	498
øD2	200	225	260	280	300	350	415	455	500	630	800
H	170	170	195	230	230	270	320	385	385	470	570



NAČIN NAROČANJA / HOW TO ORDER:

PB-3	315	/	ø248	S	ISO 6mm
					dodatki / supplements PR - prečka / traverse L - loputa / damper PP - perforacija / perforated plate ISO - izolacija / insulation 6 mm, 10 mm, 13 mm, 19 mm LD - gumijasto tesnilo / rubber seal pozicija priključka / connection position S - horizontalen / horizontal V - vertikalni / vertical priključek øD1 / connection opening øD1 standard poljuben / optional dimenzija komore / plenum dimension standard 100, 125, 160, 180, 200, 250, 315, 355, 400, 500, 630 poljuben / optional tip komore / plenum box type