



RR

REGULACIJSKA ZAŠČITNA REŠETKA ADJUSTABLE PROTECTIVE GRILL

OPIS:

Regulacijska zaščitna rešetka se vgradi na odprtino za dovod in odvod zraka na steno ali na vrata. Rešetka ima horizontalno nameščene gibljive lamele, s katerimi reguliramo količino zraka. Pozicija lamel se nastavi centralno z vijakom na okvirju.

KONSTRUKCIJA:

- nosilni okvir
- horizontalne lamele,
- mehanizem za ročno centralno nastavljanje kota lamel

MATERIAL:

- ZN - pocinkana pločevina
- AL - aluminijasta pločevina
- INOX - nerjaveča pločevina

DODATKI:

- perforirana zaščitna mreža 15x15 mm, ki preprečuje vdor malih živali, listja in večjih insektov v prezračevalni kanal
- VO - vgradni okvir
- PO - proti okvir za vgradnjo na vrata
- poljubna barva po RAL lestvici

DESCRIPTION:

The control grill is installed at the air intake and discharge opening on the wall or on the door. The grill has horizontally mounted flexible blades which regulate the air volume. The position of the blades is adjusted centrally by a screw on the frame.

CONSTRUCTION:

- supporting frame
- horizontal blades
- manual central blade angle adjustment mechanism


MATERIAL:

- ZN - galvanized sheet metal
- AL - aluminium sheet metal
- INOX - stainless steel sheet metal

SUPPLIMENTS:

- 15x15 mm perforated mesh to prevent small animals, leaves and larger insects from entering the ventilation canal
- VO - installation built-in frame
- PO - counter frame for door mounting
- RAL colour

DIMENZIJE / DIMENSIONS:



Standardne dimenzije in prosti preseki A_{ef} (m²): / Standard dimensions and free sections A_{ef} (m²):

A/B	100	200	300	400	500	600
200	0,013	0,030	0,047	0,063	0,080	0,097
300	0,020	0,047	0,073	0,100	0,126	0,153
400	0,027	0,064	0,100	0,136	0,172	0,209
500	0,035	0,081	0,127	0,173	0,219	0,265
600	0,042	0,098	0,153	0,209	0,265	0,320

Na željo kupca izdelamo tudi nestandardno dimenzijo.
Production of a non-standard dimension is possible on request.

MONTAŽA:/ INSTALLATION:

Na steno z vijaki

To the wall with screws

Na steno s pomočjo
vijakov in vzdane
vgradnega okvirja (VO)


To the wall using screws
and a built-in frame (VO)

Na vrata s perforirano
masko na nasprotni strani

On the door with a
perforated mask on the
opposite side

Na vrata s proti okvirjem
(PO) na nasprotni strani

On the door with a
counter-frame (PO) on the
opposite side of a door



NAČIN NAROČANJA / HOW TO ORDER:

RR	400	x	200	ZN	VO
					dodatki / supplements perforirana zaščitna mreža / perforated protection net VO - vgradni okvir / build-in frame PO - proti okvir / counter frame RAL barva / RAL colour material ZN, AL, INOX višina B/ height B standard 200, 300, 400, 500, 600 mm poljubna / optional širina A/ width A standard 200, 300, 400, 500, 600 mm poljubna / optional tip rešetke / type of grille